

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
11590/11520	15.875	42.862	14.288	14.288	9.525	1.5	1.5	15.9	17.6	12.8	0.70	0.9	0.10
LM11949/LM11910	19.050	45.237	15.494	16.637	12.065	1.3	1.3	29.6	30.3	9.9	0.30	2.0	0.12
M12649/M12610	21.430	50.005	17.526	18.288	13.970	1.3	1.3	39.3	41.0	10.9	0.28	2.2	0.17
1986/1922	25.400	57.150	19.845	19.355	15.875	1.3	1.5	41.6	45.7	14.2	0.33	1.8	0.24
23100/23256	25.400	65.088	22.225	21.463	15.875	1.5	1.5	48.3	52.6	20.1	0.73	0.8	0.37
L44643/L44610	25.400	50.292	14.224	14.680	10.610	-	-	27.4	31.5	10.7	0.37	1.6	0.13
M84548/M84510	25.400	57.150	19.431	19.431	14.732	1.5	1.5	41.0	48.4	16.1	0.55	1.1	0.24
L44649/L44610	26.988	50.292	14.224	14.680	10.610	-	-	27.4	31.5	10.7	0.37	1.6	0.12
15106/15250X	27.000	63.500	20.638	20.638	15.875	0.8	1.5	42.0	52.4	14.9	0.35	1.7	0.31
15580/15520	27.000	57.150	17.462	17.462	13.495	3.5	1.5	42.5	49.0	12.6	0.35	1.7	0.21
J15585/J15520	28.000	57.150	17.462	17.462	13.495	3.5	1.5	42.5	49.0	12.6	0.35	1.7	0.20
02474/02420	28.575	68.262	22.225	22.225	17.462	0.8	1.5	54.0	62.5	16.3	0.41	1.5	0.40
02872/02820	28.575	73.025	22.225	22.225	17.462	0.8	3.3	54.0	64.0	18.6	0.45	1.3	0.48
15112/15245	28.575	62.000	19.050	20.638	14.288	3.5	1.3	48.0	56.3	14.9	0.35	1.7	0.27
15112/15250	28.575	63.500	20.638	20.638	15.875	3.5	1.3	48.0	56.3	14.9	0.35	1.7	0.31
1985/1922	28.575	57.150	19.845	19.355	15.875	0.8	1.5	41.8	46.0	14.2	0.33	1.8	0.22
1988/1922	28.575	57.150	19.845	19.355	15.875	3.5	1.5	41.8	46.0	14.2	0.33	1.8	0.22
41125/41286	28.575	72.626	24.608	24.257	17.462	4.8	1.5	61.2	59.5	20.9	0.60	1.0	0.47
M86647/M86610	28.575	64.292	21.433	21.433	16.670	1.5	1.5	55.7	71.7	18.2	0.55	1.1	0.35
L45449/L45410	29.000	50.292	14.224	14.732	10.668	3.5	1.3	28.7	36.5	10.6	0.37	1.6	0.11
2691/2620	29.367	63.100	23.812	25.433	19.050	0.8	-	66.2	74.9	14.5	0.25	2.4	0.35
15117/15245	29.987	62.000	19.050	20.638	14.288	1.2	1.2	42.4	48.2	13.4	0.35	1.7	0.26
17118/17244	29.987	62.000	16.002	16.566	14.288	1.6	1.6	36.1	38.6	12.7	0.38	1.6	0.22
14117A/14276	30.000	69.012	19.845	19.583	15.875	3.6	1.2	43.8	52.3	15.5	0.38	1.6	0.36
15116/15245	30.112	62.000	19.050	20.638	14.288	0.8	1.2	42.4	48.2	13.4	0.35	1.7	0.26
17119/17244	30.162	62.000	16.002	16.566	14.288	1.6	1.6	36.1	38.6	12.7	0.38	1.5	0.23
M86649/M86610	30.162	64.292	21.433	21.433	16.670	1.5	1.5	55.7	71.7	18.2	0.55	1.1	0.34
M88043/M88010	30.162	68.262	22.225	22.225	17.462	2.3	1.5	53.3	70.8	19.3	0.55	1.1	0.41

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
15118/15245	30.213	62.000	19.050	20.638	14.288	3.6	1.2	42.4	48.2	13.4	0.35	1.7	0.26
15119/15245	30.213	62.000	19.050	20.638	14.288	1.6	1.2	42.4	48.2	13.2	0.35	1.7	0.26
15120/15245	30.213	62.000	19.050	20.638	14.288	0.8	1.2	42.4	48.2	13.4	0.35	1.7	0.26
15120/15250	30.213	63.500	20.638	20.638	15.875	0.8	1.3	45.0	54.0	14.9	0.35	1.7	0.29
14116/14274	30.226	69.012	19.845	19.583	15.875	0.8	3.3	43.0	58.0	14.0	0.38	1.6	0.36
02475/02420	31.750	68.262	22.225	22.225	17.462	3.5	1.5	56.6	66.6	16.3	0.41	1.5	0.37
02476/02420	31.750	68.262	22.225	22.225	17.462	0.8	1.6	56.6	66.6	16.3	0.41	1.5	0.38
02875/02820	31.750	73.025	22.225	22.225	17.462	3.6	3.2	52.3	62.4	17.1	0.45	1.3	0.44
02876/02820	31.750	73.025	22.225	22.225	17.462	0.8	3.2	52.3	62.4	17.1	0.45	1.3	0.45
08125/08231	31.750	58.738	164.684	15.080	10.716	1.0	1.0	28.0	31.6	14.2	0.48	1.3	0.16
14124/14276	31.750	69.012	19.845	19.583	15.875	0.8	1.3	43.0	58.0	14.0	0.38	1.6	0.35
14125A/14276	31.750	69.012	19.845	19.583	15.875	3.5	1.3	43.0	58.0	14.0	0.38	1.6	0.35
15123/15245	31.750	62.000	18.161	19.050	14.288	-	1.3	43.7	49.7	13.3	0.35	1.7	0.24
15123/15250	31.750	63.500	19.749	19.050	15.875	-	1.3	43.7	49.7	14.9	0.35	1.7	0.27
15126/15245	31.750	62.000	19.050	20.638	14.288	0.8	1.3	42.0	52.4	14.9	0.35	1.7	0.24
2580/2520	31.750	66.421	25.400	25.357	20.638	0.8	3.2	70.9	84.2	16.0	0.27	2.2	0.39
2580/2523	31.750	69.850	23.812	25.357	19.050	0.8	1.3	70.9	84.2	14.5	0.27	2.2	0.45
43125/43312	31.750	79.375	25.400	24.074	17.462	1.6	1.6	65.9	68.9	23.7	0.67	0.9	0.57
HM88542/HM88510	31.750	73.025	29.370	27.783	23.020	1.3	3.3	74.4	101.0	23.3	0.55	1.1	0.61
HM88542/HM88512	31.750	73.812	29.370	27.783	23.020	1.2	3.2	70.6	96.0	23.4	0.55	1.1	0.63
LM67048/LM67010	31.750	59.131	15.875	16.764	11.811	-	1.3	35.9	43.1	13.0	0.41	1.5	0.19
LM67049A/LM67010	31.750	59.131	15.875	16.764	11.811	0.8	1.3	36.6	45.3	13.0	0.41	1.5	0.19
M88046/M88010	31.750	68.262	22.225	22.225	17.462	1.5	1.5	53.3	70.8	19.3	0.55	1.1	0.40
26131/26283	33.338	72.000	19.000	18.923	15.875	3.6	1.6	45.1	47.1	15.3	0.36	1.7	0.34
2790/2720	33.338	76.200	23.812	25.654	19.050	1.5	3.3	74.0	92.2	15.9	0.30	2.0	0.54
43131/43312	33.338	79.375	25.400	24.074	17.462	3.6	1.6	65.9	68.9	23.7	0.67	0.9	0.55
43132/43312	33.338	79.375	25.400	24.074	17.462	2.0	1.6	65.9	68.9	23.6	0.67	0.9	0.56
44131/44348	33.338	88.501	25.400	23.698	17.462	2.0	1.6	71.5	80.2	27.9	0.78	0.8	0.76

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
HM88547/HM88510	33.338	73.025	29.370	27.783	23.020	0.8	3.3	74.4	101.0	23.3	0.55	1.1	0.59
HM89443/HM89410	33.338	76.200	29.370	28.575	23.020	0.8	3.2	75.5	101.7	23.9	0.55	1.1	0.66
M88047/M88010	33.338	68.262	22.225	22.225	17.462	5.5	1.5	53.3	70.8	19.3	0.55	1.1	0.37
M88048/M88010	33.338	68.262	22.225	22.225	17.462	0.8	1.5	53.3	70.8	19.3	0.55	1.1	0.38
M88048/M88011	33.338	68.262	22.225	22.225	17.462	0.8	2.3	53.3	70.8	19.3	0.55	1.1	0.38
02877/02820	34.925	73.025	22.225	22.225	17.462	3.6	3.2	52.3	62.4	18.5	0.45	1.3	0.41
02878/02820	34.925	73.025	22.225	22.225	17.462	0.8	3.2	52.3	62.4	18.5	0.45	1.3	0.42
14136A/14276	34.925	69.012	26.982	18.288	13.970	-	1.2	43.7	52.3	15.5	0.38	1.6	0.31
14138A/14274	34.925	69.012	19.845	19.583	15.875	3.5	3.3	43.0	58.0	14.0	0.38	1.6	0.32
14138A/14276	34.925	69.012	19.845	19.583	15.875	3.5	1.3	43.0	58.0	14.0	0.38	1.6	0.32
16137/16284	34.925	72.238	20.638	20.638	15.875	3.6	1.2	47.2	58.2	16.6	0.40	1.5	0.32
23690/23620	34.925	73.025	26.988	26.975	22.225	3.6	1.6	73.9	89.4	18.7	0.37	1.6	0.50
25877/25821	34.925	73.025	23.812	24.608	19.050	1.5	0.8	71.5	86.7	15.7	0.29	2.1	0.47
25877/28520	34.925	73.025	23.812	24.608	19.050	1.5	2.3	71.5	86.7	15.7	0.29	2.1	0.46
2793/2720	34.925	76.200	23.812	25.654	19.050	0.8	3.3	74.0	92.2	15.9	0.30	2.0	0.49
2793/2735X	34.925	73.025	23.812	25.654	19.050	0.8	0.8	74.0	92.2	15.9	0.30	2.0	0.44
28137/28317	34.925	80.035	21.433	20.940	15.875	1.6	1.2	54.4	62.6	15.9	0.40	1.5	0.50
31594/31520	34.925	76.200	29.370	28.575	23.812	1.6	3.2	76.9	92.5	21.5	0.40	1.5	0.62
3379/3320	34.925	80.167	29.370	30.391	23.812	3.5	3.3	98.9	117.6	18.1	0.27	2.2	0.73
3478/3420	34.925	79.375	29.370	29.771	23.812	3.6	3.2	83.0	99.8	20.7	0.37	1.6	0.70
449/432	34.925	95.250	27.783	29.901	22.225	0.8	2.4	97.9	115.9	18.4	0.28	2.1	1.07
HM88649/HM88610	34.925	72.233	25.400	25.400	19.842	2.3	2.3	67.0	87.3	20.7	0.55	1.1	0.49
HM89446/HM89410	34.925	76.200	29.370	28.575	23.020	3.5	3.3	79.6	106.7	22.5	0.55	1.1	0.65
HM89446/HM89411	34.925	76.200	29.370	28.575	23.020	3.5	0.8	79.6	106.7	22.5	0.55	1.1	0.64
LM48548/LM48510	34.925	65.088	18.034	18.288	13.970	-	1.3	42.4	54.0	14.3	0.38	1.6	0.25
339/332	35.000	80.000	21.000	22.403	17.826	0.8	1.2	64.6	71.1	15.1	0.27	2.2	0.53
L68149/L68110	35.000	59.131	15.875	16.764	11.938	-	1.3	37.4	50.7	13.1	0.42	1.4	0.17
L68149/L68111	35.000	60.000	15.875	16.764	11.938	-	1.3	37.4	50.7	13.1	0.42	1.4	0.18

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
LM78349/LM78310	35.000	62.000	16.700	17.000	13.600	-	1.0	34.1	49.4	14.4	0.44	1.4	0.21
HM88648/HM88610	35.717	72.233	25.400	25.400	19.842	3.6	2.4	67.0	87.3	20.7	0.55	1.1	0.48
2780/2720	36.487	76.200	23.812	25.654	19.050	1.5	3.3	74.0	92.2	15.9	0.30	2.0	0.57
3479/3420	36.512	79.375	29.370	29.771	23.812	0.8	3.2	83.0	99.8	20.7	0.37	1.6	0.68
3878/3820	36.512	85.725	30.162	30.162	23.812	0.8	3.2	102.6	129.2	22.9	0.40	1.5	0.89
44143/44348	36.512	88.501	25.400	23.698	17.462	2.1	1.6	71.5	80.2	27.9	0.78	0.8	0.72
HM89249/HM89210	36.512	79.375	29.370	28.829	22.664	3.5	3.3	89.3	108.9	23.7	0.55	1.1	0.69
HM89449/HM89410	36.512	76.200	29.370	28.575	23.020	3.5	3.3	71.6	107.1	23.7	0.55	1.1	0.63
HM89449/HM89411	36.512	76.200	29.370	28.575	23.020	3.6	0.8	79.6	106.7	23.9	0.55	1.1	0.70
JL69349/JL69310	38.000	63.000	17.000	17.000	13.500	-	1.3	40.9	55.4	14.7	0.42	1.4	0.20
13687/13621	38.100	65.088	19.812	18.288	15.748	2.4	1.2	40.8	53.7	16.1	0.44	1.4	0.29
13889/13830	38.100	63.500	12.700	11.908	9.525	1.6	0.8	24.2	31.4	11.9	0.35	1.7	0.14
13889/13836	38.100	65.088	12.700	11.908	9.525	1.6	0.8	24.2	31.4	11.9	0.35	1.7	0.15
16150/16282	38.100	72.000	19.000	20.638	14.237	3.5	1.5	51.8	64.5	15.3	0.40	1.5	0.34
16150/16283	38.100	72.238	23.812	20.638	19.050	3.6	2.4	47.2	58.2	19.8	0.40	1.5	0.33
16150/16284	38.100	72.238	20.638	20.638	15.875	3.5	1.5	51.8	64.5	16.9	0.40	1.5	0.35
2788/2720	38.100	76.200	23.812	25.654	19.050	3.5	3.3	74.0	92.2	15.9	0.30	2.0	0.49
28150/28317	38.100	80.035	21.432	20.940	15.875	1.6	1.6	54.4	62.6	16.9	0.40	1.5	0.48
3490/3420	38.100	79.375	29.370	29.771	23.812	3.6	3.2	82.7	99.8	20.7	0.37	1.6	0.65
418/414	38.100	88.500	26.988	29.083	22.225	3.5	1.5	99.2	113.2	17.4	0.26	2.3	0.84
HM801346/HM801310	38.100	82.550	29.370	28.575	23.020	0.8	3.3	79.8	117.5	24.3	0.55	1.1	0.77
LM29748/LM29710	38.100	65.088	18.034	18.288	13.970	3.5	1.3	43.3	56.8	13.8	0.33	1.8	0.23
LM29749/LM29710	38.100	65.088	18.034	18.288	13.970	2.3	1.3	43.3	56.8	13.8	0.33	1.8	0.23
LM29749/LM29711	38.100	65.088	19.812	18.288	15.748	2.3	1.3	43.3	56.8	15.5	0.33	1.8	0.24
2789/2720	39.688	76.200	23.812	25.654	19.050	3.5	3.3	74.0	92.2	15.9	0.30	2.0	0.47
2789/2735X	39.688	73.025	23.812	25.654	19.050	3.5	0.8	74.0	92.2	15.9	0.30	2.0	0.47
M201047/M201011	39.688	73.025	25.654	22.098	21.336	0.8	2.3	68.8	90.8	19.0	0.33	1.8	0.44
28158/28300	40.000	76.200	20.638	20.940	15.507	1.5	1.3	58.1	67.0	16.1	0.40	1.5	0.38

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
18590/18520	41.275	73.025	16.667	17.462	12.700	3.5	1.5	45.7	55.3	14.5	0.35	1.7	0.28
2014949/2014910	41.275	73.431	21.430	19.812	16.604	3.5	0.8	58.3	73.2	18.2	0.40	1.5	0.36
24780/24720	41.275	76.200	22.225	23.020	17.462	3.5	0.8	66.0	82.8	17.4	0.39	1.5	0.42
24780/24721	41.275	76.200	25.400	23.020	20.638	3.5	2.3	66.0	82.8	20.6	0.39	1.5	0.46
26882/26820	41.275	80.167	25.400	25.400	20.638	3.5	3.3	76.4	98.1	18.0	0.32	1.9	0.55
336/332	41.275	80.000	21.000	22.403	17.826	0.8	1.2	64.6	71.1	15.1	0.27	2.2	0.46
3384/3320	41.275	80.167	29.370	30.391	23.812	0.8	3.3	98.9	117.6	18.1	0.27	2.2	0.64
342/332	41.275	80.000	21.000	22.403	17.826	3.6	1.2	64.6	71.1	15.1	0.27	2.2	0.45
3585/3525	41.275	87.312	30.162	30.886	23.812	1.5	3.3	94.0	117.0	19.9	0.31	2.0	0.84
365A/362A	41.275	88.900	20.638	22.225	16.513	3.6	1.2	70.6	82.9	16.1	1.88	1.0	0.62
3877/3821	41.275	85.725	30.162	30.886	23.812	0.8	3.2	102.6	129.2	22.9	0.40	1.5	0.82
419/414	41.275	88.501	26.988	29.083	22.225	3.6	1.6	93.3	106.4	16.9	0.26	2.3	0.77
4388/4335	41.275	90.488	39.688	40.386	33.338	3.6	3.2	125.4	160.6	25.6	0.28	2.1	1.23
46162/46368	41.275	93.662	31.750	31.750	26.195	0.8	3.2	99.8	127.3	24.0	0.40	1.5	1.07
49162/49368	41.275	93.662	31.750	31.750	25.400	3.5	3.3	116.9	142.6	21.9	0.36	1.7	1.05
526/522	41.275	101.600	34.925	36.068	26.988	3.6	3.2	124.5	151.1	22.2	0.29	2.1	1.32
HM803145/HM803110	41.275	88.900	30.162	29.370	23.020	0.8	3.2	100.9	127.4	26.3	0.55	1.1	0.90
HM803146/HM803110	41.275	88.900	30.163	29.370	23.020	3.5	3.3	100.9	127.4	26.3	0.55	1.1	0.89
HM804840/HM804810	41.275	95.250	30.162	29.370	23.020	3.6	3.2	98.8	133.0	26.5	0.55	1.1	1.06
HM807035/HM807010	41.275	104.775	36.512	36.512	28.575	1.6	3.2	134.0	185.3	29.3	0.49	1.2	1.69
LM501349/LM501310	41.275	73.431	19.558	19.812	14.732	3.5	0.8	58.3	73.2	16.3	0.40	1.5	0.35
LM501349/LM501311	41.275	73.431	23.012	19.812	18.186	3.6	2.4	54.9	69.4	19.5	0.40	1.5	0.33
LM501349/LM501314	41.275	73.431	21.430	19.812	16.604	3.5	0.8	58.3	73.2	18.2	0.40	1.5	0.36
M802048/M802011	41.275	82.550	26.543	25.654	20.193	3.5	3.3	77.5	118.3	23.2	0.55	1.1	0.62
4395/4335	42.070	90.488	39.688	40.386	33.338	3.6	3.2	125.4	160.6	25.6	0.28	2.1	1.21
12168/12303	42.862	76.992	17.462	17.145	11.908	1.6	1.6	42.8	53.7	17.5	0.51	1.2	0.31
22780/22720	42.862	82.550	26.195	26.988	20.638	3.5	3.3	80.1	105.4	20.0	0.40	1.5	0.61
25577/25520	42.875	82.931	23.812	25.400	19.050	3.5	0.8	78.2	101.4	17.3	0.33	1.8	0.58

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
25577/25522	42.875	83.058	23.876	25.400	19.114	3.5	2.0	78.2	101.4	17.4	0.33	1.8	0.58
25577/25523	42.875	82.931	26.988	25.400	22.225	3.5	2.3	78.2	101.4	20.5	0.33	1.8	0.62
12175/12303	44.450	76.992	17.462	17.145	11.908	1.6	1.6	42.8	53.7	17.5	0.51	1.2	0.30
18685/18620	44.450	79.375	17.462	17.462	13.495	2.8	1.5	42.7	52.5	15.2	0.37	1.6	0.35
25580/25520	44.450	82.931	23.812	25.400	19.050	3.5	0.8	78.2	101.4	17.3	0.33	1.8	0.56
25580/25521	44.450	83.058	23.812	25.400	19.050	3.5	3.3	78.2	101.4	17.3	0.33	1.8	0.55
25580/25523	44.450	82.931	26.988	25.400	22.225	3.5	2.3	78.2	101.4	20.5	0.33	1.8	0.60
25582/25520	44.450	82.931	23.812	25.400	19.050	5.2	0.8	73.3	95.0	17.5	0.33	1.8	0.55
33885/33821	44.450	95.250	27.783	28.575	22.225	0.8	2.4	102.6	134.0	20.4	0.33	1.8	0.96
355/354A	44.450	85.000	20.638	21.692	17.462	2.4	1.2	68.2	77.6	15.5	0.31	2.0	0.50
355A/354A	44.450	85.000	20.638	21.692	17.462	0.8	1.2	68.2	77.6	15.5	0.31	2.0	0.50
3782/3720	44.450	93.264	30.162	30.302	23.812	3.5	3.3	103.2	136.7	21.5	0.34	1.8	0.96
438/429XS	44.450	90.000	30.958	29.900	25.400	3.5	-	110.5	133.0	21.7	0.28	2.1	0.85
438/432A	44.450	95.250	27.783	29.901	22.225	3.6	0.8	97.9	115.9	18.4	0.28	2.1	0.93
46175/46368	44.450	93.662	31.750	31.750	26.195	0.8	3.2	99.8	127.3	24.0	0.40	1.5	1.01
46176/46368	44.450	93.662	31.750	31.750	26.195	3.6	3.2	99.8	127.3	24.0	0.40	1.5	1.01
49175/49368	44.450	93.662	31.750	31.750	25.400	3.6	3.2	99.8	116.9	22.9	0.36	1.7	1.00
49576/49520	44.450	98.425	30.162	31.750	25.400	0.8	3.2	108.3	135.9	23.9	0.40	1.5	1.23
527/522	44.450	101.600	34.925	36.068	26.988	3.6	3.2	124.5	151.1	22.2	0.29	2.1	1.35
53177/53375	44.450	95.250	30.958	28.301	20.638	3.6	0.8	84.3	93.5	29.9	0.74	0.8	0.94
53178/53375	44.450	95.250	30.958	28.301	20.638	2.0	0.8	84.3	93.5	30.0	0.74	0.8	0.94
535/532A	44.450	111.125	38.100	36.957	30.162	3.6	3.2	131.1	163.4	23.9	0.30	2.0	1.84
55175C/55437	44.450	111.125	30.162	26.909	20.638	3.5	3.3	113.9	153.8	37.9	0.88	0.7	1.45
HM803149/HM803110	44.450	88.900	30.162	29.370	23.020	3.5	3.3	100.9	127.4	26.3	0.55	1.1	0.84
HM803149/HM803112	44.450	92.075	30.162	29.370	23.020	3.5	3.3	100.9	127.4	26.3	0.55	1.1	0.92
HM804842/HM804810	44.450	95.250	30.162	29.370	23.020	0.8	2.4	98.8	133.0	26.5	0.55	1.1	1.02
HM804843/HM804810	44.450	95.250	30.162	29.370	23.020	3.6	2.4	98.8	133.0	26.5	0.55	1.1	1.01
HM807040/HM807010	44.450	104.775	36.512	36.512	28.575	3.5	3.3	145.9	202.5	29.2	0.49	1.2	1.61

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
HM903249/HM903210	44.450	95.250	30.958	28.575	22.225	3.5	0.8	100.7	121.5	30.8	0.74	0.8	0.99
L102849/L102810	44.450	73.025	18.258	18.258	15.083	1.6	1.6	44.8	62.2	14.5	0.32	1.9	0.30
STB4489	44.450	88.900	30.163	29.370	20.600	3.5	3.3	89.9	111.8	28.8	0.70	0.9	0.81
3776/3720	44.983	93.264	30.162	30.302	23.812	3.6	3.2	97.9	130.2	22.1	0.34	1.8	0.94
HM903248/HM903210	44.988	95.250	30.958	28.575	22.225	3.6	0.8	94.7	114.0	30.8	0.74	0.8	0.99
358/354A	45.000	85.000	20.638	21.692	17.462	1.6	1.2	68.2	77.6	15.5	0.31	2.0	0.50
17887/17831	45.230	79.985	19.842	20.638	15.080	2.0	1.3	61.0	76.0	16.1	0.37	1.6	0.41
LM102949/LM102910	45.242	73.431	19.558	19.812	15.748	3.5	0.8	55.9	78.1	14.6	0.31	2.0	0.31
LM603049/LM603011	45.242	77.788	19.842	19.842	15.080	3.5	0.8	57.7	73.7	17.4	0.43	1.4	0.36
LM603049/LM603012	45.242	77.788	21.430	19.842	16.667	3.5	0.8	57.7	73.7	19.0	0.43	1.4	0.38
LM603049/LM603014	45.242	79.974	19.842	19.842	15.080	3.6	0.8	57.7	73.7	17.5	0.43	1.4	0.39
25590/25520	45.618	82.931	23.812	25.400	19.050	3.5	0.8	78.2	101.4	17.3	0.33	1.8	0.54
25590/25522	45.618	83.058	23.876	25.400	19.114	3.5	2.0	78.2	101.4	17.4	0.33	1.8	0.55
25590/25523	45.618	82.931	26.988	25.400	22.225	3.5	2.3	78.2	101.4	20.5	0.33	1.8	0.58
25590/25526	45.618	85.000	23.812	25.400	19.050	3.6	2.4	78.2	101.4	17.5	0.33	1.8	0.57
18690/18620	46.038	79.375	17.462	17.462	13.495	2.8	1.5	47.0	58.6	15.2	0.37	1.6	0.33
2984/2924	46.038	85.000	25.400	25.608	20.638	3.5	1.3	81.3	108.1	19.0	0.35	1.7	0.61
359A/354A	46.038	85.000	20.638	21.692	17.462	3.6	1.2	68.2	77.6	15.5	0.31	2.0	0.48
359S/354A	46.038	85.000	20.638	21.692	17.462	2.4	1.2	68.2	77.6	15.5	0.31	2.0	0.48
369A/362A	47.625	88.900	20.638	22.225	16.513	3.6	1.2	70.6	82.9	16.1	0.32	1.9	0.54
386A/382A	47.625	96.838	21.000	21.946	15.875	0.8	0.8	81.5	102.2	18.0	0.35	1.7	0.73
45282/45220	47.625	104.775	30.162	30.958	23.812	3.6	3.2	119.7	156.8	22.2	0.33	1.8	1.26
463/453X	47.625	104.775	30.162	29.317	24.605	4.8	3.2	103.6	136.8	23.6	0.34	1.8	1.21
467/453X	47.625	104.775	30.162	29.317	24.605	0.8	3.2	103.6	136.8	23.6	0.34	1.8	1.22
528/522	47.625	101.600	34.925	36.068	26.988	3.6	3.2	124.5	151.1	22.2	0.29	2.1	1.29
536/532X	47.625	107.950	36.512	36.957	28.575	3.5	3.3	145.9	185.3	24.2	0.30	2.0	1.58
55187/55437	47.625	111.125	30.162	26.909	20.638	3.6	3.2	92.8	113.1	36.6	0.88	0.7	1.39
HM804846/HM804810	47.625	95.250	30.162	29.370	23.020	3.6	3.2	98.8	133.0	26.5	0.55	1.1	0.96

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
M804049/M804010	47.625	88.900	25.400	25.400	19.050	3.6	3.2	82.7	106.4	23.2	0.55	1.1	0.65
HM804848/HM804810	48.412	95.250	30.162	29.370	23.020	2.4	3.2	98.8	133.0	26.5	0.55	1.1	0.95
HM804849/HM804810	48.412	95.250	30.162	29.370	23.020	3.6	3.2	98.8	133.0	26.5	0.55	1.1	0.95
365S/362A	49.212	88.900	20.638	22.225	16.513	0.8	1.2	70.6	82.9	16.1	0.32	1.9	0.53
65390/65320	49.212	114.300	44.450	44.450	34.925	3.6	3.2	179.6	218.5	31.7	0.43	1.4	2.18
HH506348/HH506310	49.212	114.300	44.450	44.450	36.068	3.6	3.2	201.4	249.9	30.5	0.40	1.5	2.34
HM807044/HM807010	49.212	104.775	36.512	36.512	28.575	3.6	3.2	145.9	202.5	29.3	0.49	1.2	1.52
365/362A	50.000	88.900	20.638	22.225	16.513	2.0	1.2	70.6	82.9	16.1	0.32	1.9	0.51
366/362A	50.000	88.900	20.638	22.225	16.513	2.4	1.2	70.6	82.9	16.1	0.32	1.9	0.51
396/394A	50.000	110.000	22.000	21.996	18.824	0.8	1.2	82.1	110.2	21.3	0.40	1.5	1.04
JHM807045/JHM807012	50.000	105.000	37.000	36.000	29.000	3.0	2.8	141.6	194.8	29.4	0.49	1.2	1.52
JLM104948/JLM104910	50.000	82.000	21.500	21.500	17.000	3.0	0.5	77.2	105.3	16.4	0.31	2.0	0.42
JM205149/JM205110	50.000	90.000	28.000	28.000	23.000	3.0	2.5	107.4	142.9	20.0	0.33	1.8	0.75
18200/18337	50.800	85.725	19.050	18.263	12.700	1.6	1.6	48.2	63.1	20.9	0.57	1.1	0.39
18790/18720	50.800	85.000	17.462	17.462	13.495	3.5	1.5	49.6	64.9	16.8	0.41	1.5	0.37
18790/18724	50.800	88.900	17.462	17.462	13.495	3.6	1.2	47.2	62.2	17.3	0.41	1.5	0.42
28580/28521	50.800	92.075	24.608	25.400	19.845	3.5	0.8	85.2	118.4	20.0	0.38	1.6	0.70
28678/28622	50.800	97.630	24.608	24.608	19.446	3.6	0.8	85.1	124.5	21.2	0.40	1.5	0.83
33889/33821	50.800	95.250	27.783	28.575	22.225	-	2.3	110.5	145.9	20.1	0.33	1.8	0.84
368/362	50.800	90.000	20.000	22.225	15.875	1.5	2.0	77.7	92.8	15.9	0.32	1.9	0.53
368/362A	50.800	88.900	20.638	22.225	16.513	1.5	1.3	77.7	92.8	16.6	0.32	1.9	0.52
368A/362	50.800	90.000	20.000	22.225	15.875	3.5	2.0	77.7	92.8	15.9	0.32	1.9	0.52
368A/362A	50.800	88.900	20.638	22.225	16.513	3.5	1.3	77.7	92.8	16.6	0.32	1.9	0.51
368A/362X	50.800	90.000	25.000	22.225	20.000	3.5	2.0	77.7	92.8	20.9	0.32	1.9	0.59
370A/362A	50.800	88.900	20.638	22.225	16.513	5.2	1.2	70.6	82.9	16.1	0.32	1.9	0.49
375/374	50.800	93.264	20.638	22.225	15.083	2.4	1.2	80.2	93.6	16.8	0.34	1.8	0.59
3780/3720	50.800	93.264	30.162	30.302	23.812	3.5	3.3	103.2	136.7	21.5	0.34	1.8	0.85
3780/3730	50.800	93.264	30.162	30.302	23.812	3.6	0.8	103.2	136.7	22.1	0.34	1.8	0.85

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
3780/3732	50.800	98.425	30.162	30.302	23.812	3.6	3.2	97.9	130.2	22.2	0.34	1.8	0.98
385AX/382A	50.800	96.838	21.000	21.946	15.875	0.8	0.8	76.4	96.0	17.4	0.35	1.7	0.68
39575/39520	50.800	112.712	30.162	30.162	23.812	3.6	3.2	147.0	207.0	23.3	0.34	1.8	1.49
45284/45220	50.800	104.775	30.162	30.958	23.812	6.4	3.2	126.0	165.0	22.2	0.33	1.8	1.19
4580/4535	50.800	104.775	39.688	40.157	33.338	3.6	3.2	151.0	211.0	27.2	0.34	1.8	1.61
49585/49520	50.800	101.600	31.750	31.750	25.400	3.5	3.3	114.3	142.8	24.8	0.40	1.5	1.14
529/522	50.800	101.600	34.925	36.068	26.988	0.8	3.2	131.0	159.0	22.2	0.29	2.1	1.23
529X/522	50.800	101.600	34.925	36.068	26.988	3.6	3.2	131.0	159.0	22.2	0.29	2.1	1.22
537/532X	50.800	107.950	36.512	36.957	28.575	3.6	3.2	138.0	172.0	24.2	0.30	2.0	1.52
55200/55437	50.800	111.125	30.162	26.909	20.638	3.6	3.2	113.9	153.8	36.6	0.88	0.7	1.34
55200C/55437	50.800	111.125	30.162	26.909	20.638	3.5	3.3	113.9	153.8	37.9	0.88	0.7	1.35
59200/59412	50.800	104.775	36.512	36.512	28.575	3.6	3.2	148.0	187.0	26.9	0.40	1.5	1.39
619/612	50.800	120.650	41.275	41.275	31.750	3.6	3.2	174.0	217.0	27.3	0.31	1.9	2.26
65200/65500	50.800	127.000	44.450	44.450	34.925	3.6	3.2	208.0	269.0	35.2	0.49	1.2	2.87
72200C/72487	50.800	123.825	36.512	32.791	25.400	3.5	3.3	158.8	195.4	38.2	0.74	0.8	2.02
HM807046/HM807010	50.800	104.775	36.512	36.512	28.575	3.5	3.3	145.9	202.5	29.2	0.49	1.2	1.48
HM907643/HM907614	50.800	111.125	30.162	28.575	20.638	3.6	3.2	107.0	142.0	37.1	0.88	0.7	1.34
LM104949/JLM104910	50.800	82.000	21.976	22.225	17.000	3.5	0.5	70.8	95.7	16.0	0.31	2.0	0.42
LM104949/LM104911	50.800	82.550	21.590	22.225	16.510	3.5	1.3	70.8	95.7	16.0	0.31	2.0	0.42
368S/362	51.592	90.000	20.000	22.225	15.875	2.0	2.0	77.7	92.8	15.9	0.32	1.9	0.48
368S/362A	51.592	88.900	20.638	22.225	16.513	2.0	1.3	77.7	92.8	16.6	0.32	1.9	0.47
28584/28521	52.388	92.075	24.608	25.400	19.845	3.5	0.8	85.2	118.4	20.0	0.38	1.6	0.67
3767/3720	52.388	93.264	30.162	30.302	23.812	2.3	3.3	103.2	136.7	21.5	0.34	1.8	0.81
468/453X	52.388	104.775	30.162	29.317	24.605	1.6	3.2	109.0	144.0	23.6	0.34	1.8	1.12
33895/33822	53.975	92.250	27.783	28.575	22.225	1.6	0.8	108.0	141.0	20.4	0.33	1.8	0.79
4549/4535	53.975	104.775	39.688	40.157	33.338	3.6	3.2	151.0	211.0	27.2	0.34	1.8	1.54
456/453X	53.975	104.775	30.162	29.317	24.605	3.6	3.2	109.0	144.0	23.6	0.34	1.8	1.10
539/532X	53.975	107.950	36.512	36.957	28.575	3.6	3.2	138.0	172.0	24.2	0.30	2.0	1.44

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
539A/532X	53.975	107.950	36.512	36.957	28.575	5.6	3.2	138.0	172.0	23.9	0.30	2.0	1.43
557S/552A	53.975	123.825	38.100	36.678	30.162	3.6	3.2	162.0	223.0	28.7	0.35	1.7	2.22
621/612	53.975	120.650	41.275	41.275	31.750	3.6	3.2	174.0	217.0	27.3	0.31	1.9	2.18
65212/65500	53.975	127.000	44.450	44.450	34.925	3.6	3.2	208.0	269.0	35.1	0.49	1.2	1.58
66584/66520	53.975	122.238	33.338	31.750	23.812	3.6	3.2	128.0	153.0	35.3	0.67	0.9	1.78
72212C/72487	53.975	123.825	36.512	32.791	25.400	3.5	3.3	158.8	195.4	38.2	0.74	0.8	2.02
HM807049/HM807010	53.975	104.775	36.512	36.512	28.575	3.6	3.2	141.0	195.0	29.3	0.49	1.2	1.41
KHM911242/KHM911210	53.975	130.175	36.512	33.338	23.812	3.5	3.3	155.5	186.1	41.9	0.82	0.7	2.26
LM806649/LM806610	53.975	88.900	19.050	19.050	13.492	2.4	2.0	62.9	86.8	21.5	0.55	1.1	0.42
466/453X	54.988	104.775	30.162	29.317	24.605	2.4	3.2	109.0	144.0	23.6	0.34	1.8	1.08
6381/6320	54.991	135.755	53.975	56.007	44.450	3.6	3.2	266.0	357.0	34.8	0.32	1.9	1.08
385/382A	55.000	96.838	21.000	21.946	15.875	2.4	0.8	80.4	101.0	17.4	0.35	1.7	0.61
385X/382A	55.000	96.838	21.000	21.946	15.875	3.6	0.8	80.4	101.0	17.4	0.35	1.7	0.61
JH307749/JH307710	55.000	110.000	39.000	39.000	32.000	3.0	2.5	176.0	224.0	27.1	0.35	1.7	1.69
JLM506849/JLM506810	55.000	90.000	23.000	23.000	18.500	1.5	0.5	79.1	111.4	20.1	0.40	1.5	0.55
JM207049/JM207010	55.000	95.000	29.000	29.000	23.500	1.5	2.5	105.0	143.0	21.6	0.34	1.8	0.83
JM207049A/JM207010	55.000	95.000	29.000	29.000	23.500	6.0	2.5	105.0	143.0	21.6	0.34	1.8	0.81
28680/28622	55.562	97.630	24.608	24.608	19.446	3.5	0.8	88.1	126.2	21.4	0.40	1.5	0.76
HM813840/HM813810	55.562	127.000	36.512	36.512	26.988	3.6	3.2	166.0	235.0	32.9	0.50	1.2	2.73
389/382A	55.575	96.838	21.000	21.946	15.875	2.4	0.8	80.4	101.0	17.4	0.35	1.7	0.60
28682/28622	57.150	97.630	24.608	24.608	19.446	3.5	0.8	88.1	126.2	21.4	0.40	1.5	0.73
33225/33462	57.150	117.475	30.162	30.162	23.812	3.6	3.2	118.0	179.0	27.8	0.44	1.4	1.53
387/382	57.150	98.425	21.000	21.946	17.826	2.3	0.8	81.5	102.2	18.0	0.35	1.7	0.64
387/382A	57.150	96.838	21.000	21.946	15.875	2.4	0.8	81.5	102.2	17.4	0.35	1.7	0.58
387/382S	57.150	96.838	25.400	21.946	20.274	2.3	2.3	81.5	102.2	22.4	0.35	1.7	0.66
387A/382A	57.150	96.838	21.000	21.946	15.875	3.5	0.8	81.5	102.2	18.0	0.35	1.7	0.59
387A/382S	57.150	96.838	25.400	21.946	20.274	3.5	2.3	81.5	102.2	22.4	0.35	1.7	0.66
387A/383A	57.150	100.000	21.000	21.946	17.826	3.5	2.0	81.5	102.2	18.0	0.35	1.7	0.67

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
387AS/382A	57.150	96.838	21.000	21.946	15.875	5.0	0.8	81.5	102.2	18.0	0.35	1.7	0.59
387AS/382S	57.150	96.838	25.400	21.946	20.274	5.0	2.3	81.5	102.2	22.4	0.35	1.7	0.66
387S/382A	57.150	96.838	21.000	21.946	15.875	0.8	0.8	81.5	102.2	18.0	0.35	1.7	0.60
387S/382S	57.150	96.838	25.400	21.946	20.274	0.8	2.3	81.5	102.2	22.4	0.35	1.7	0.66
39580/39520	57.150	112.712	30.162	30.162	23.812	3.6	3.2	147.0	207.0	23.3	0.34	1.8	1.37
39581/39520	57.150	112.712	30.162	30.162	23.812	7.9	3.2	147.0	207.0	23.3	0.34	1.8	1.33
3979/3920	57.150	112.712	30.162	30.048	23.812	3.6	3.2	111.0	164.0	25.9	0.40	1.5	1.36
45291/45221	57.150	104.775	30.162	30.958	23.812	6.4	0.8	126.0	165.0	22.2	0.33	1.8	1.05
462/453X	57.150	104.775	30.162	29.317	24.605	2.4	3.2	127.4	169.2	23.6	0.34	1.8	1.04
469/453X	57.150	104.775	29.317	30.162	24.605	3.5	3.3	127.4	169.2	23.1	0.34	1.8	1.08
623/612	57.150	120.650	41.275	41.275	31.750	3.6	3.2	174.0	217.0	27.3	0.31	1.9	2.09
65225/65500	57.150	127.000	44.450	44.450	34.925	3.6	3.2	208.0	269.0	35.1	0.49	1.2	2.68
72225C/72487	57.150	123.825	36.512	32.791	25.400	3.6	3.2	156.0	190.0	37.9	0.74	0.8	2.05
78225/78551	57.150	140.030	36.512	33.236	23.620	3.6	2.4	150.0	177.0	46.1	0.87	0.7	2.56
388A/382A	57.531	96.838	21.000	21.946	15.875	3.6	0.8	80.4	101.0	17.4	0.35	1.7	0.57
66589/66520	59.572	122.238	33.338	31.750	23.812	0.8	3.2	128.0	153.0	35.3	0.67	0.9	1.65
29580/29520	60.000	107.950	25.400	25.400	19.050	3.6	3.2	92.8	143.0	24.6	0.46	1.3	0.84
397/394A	60.000	110.000	22.000	21.996	18.824	0.8	1.2	86.4	116.0	21.3	0.40	1.5	0.89
511482M/511482	60.000	134.983	33.449	30.924	21.948	3.5	3.5	152.4	178.6	39.8	0.82	0.7	2.20
JLM508748/JLM508710	60.000	95.000	24.000	24.000	19.000	5.0	2.5	83.6	123.3	21.3	0.40	1.5	0.59
28985/28920	60.325	101.600	25.400	25.400	19.845	3.5	3.3	92.9	138.2	22.9	0.42	1.4	0.80
28985/28921	60.325	100.000	25.400	25.400	19.845	3.5	3.3	92.9	138.2	22.9	0.42	1.4	0.75
65237/65500	60.325	127.000	44.450	44.450	34.925	3.6	3.2	208.0	269.0	35.1	0.49	1.2	2.66
65237A/65500	60.325	127.000	44.450	44.450	34.925	1.6	3.2	208.0	269.0	35.1	0.49	1.2	2.59
H715332/H715311	60.325	136.525	46.038	46.038	36.512	3.6	3.2	231.0	369.0	37.0	0.47	1.3	3.55
HM813841/HM813811	60.325	127.000	36.512	36.512	26.988	3.6	1.6	166.0	235.0	32.9	0.50	1.2	2.61
HM813841A/HM813810	60.325	127.000	36.512	36.512	36.988	1.6	3.2	166.0	235.0	32.9	0.50	1.2	2.61
HM911245/HM911210	60.325	130.175	36.512	33.338	23.812	5.0	3.3	155.5	186.1	41.9	0.82	0.7	2.11

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
392/394A	61.912	110.000	22.000	21.996	18.824	0.8	1.3	88.5	119.3	21.1	0.40	1.5	0.87
29585/29520	63.500	107.950	25.400	25.400	19.050	3.5	3.3	96.9	150.2	24.4	0.46	1.3	0.90
29585/29521	63.500	110.000	25.400	25.400	19.050	-	1.3	96.9	150.2	24.4	0.46	1.3	0.97
29587/29520	63.500	107.950	25.400	25.400	19.050	5.0	3.3	96.9	150.2	24.4	0.46	1.3	0.91
390A/394A	63.500	110.000	22.000	21.996	18.824	1.5	1.3	88.5	119.3	21.1	0.40	1.5	0.85
390A/394AS	63.500	110.000	22.000	21.996	18.824	1.5	3.3	88.5	119.3	21.1	0.40	1.5	0.84
390A-EK/394A	63.500	110.000	22.000	21.996	18.824	2.5	1.3	88.5	119.3	21.1	0.40	1.5	0.85
390A-EK/394AB	63.500	114.673	22.000	21.996	18.824	2.5	1.3	88.5	119.3	21.1	0.40	1.5	0.87
395/394A	63.500	110.000	22.000	21.996	18.824	3.5	1.3	88.5	119.3	21.1	0.40	1.5	0.84
39585/39520	63.500	112.712	30.162	30.162	23.812	3.5	3.3	148.6	209.3	23.3	0.34	1.8	1.25
3982/3920	63.500	112.712	30.162	30.048	23.812	3.5	3.3	109.9	163.4	25.8	0.40	1.5	1.24
L610549/L610510	63.500	94.458	19.050	19.050	15.083	1.5	1.5	53.1	96.5	19.5	0.42	1.4	0.45
504376B/504376A	65.000	120.000	32.750	33.000	27.000	3.0	0.6	145.7	207.2	27.2	0.40	1.5	1.55
JD6549/JD6510	65.000	110.000	31.000	31.000	25.000	2.5	2.5	139.5	193.0	23.5	0.33	1.8	1.18
29590/29522	66.675	107.950	25.400	25.400	19.050	3.5	0.8	96.9	150.2	24.4	0.46	1.3	0.86
33262/33462	66.675	117.475	30.162	30.162	23.812	3.5	3.3	115.8	173.3	27.7	0.44	1.4	1.33
33262/33472	66.675	120.000	29.794	30.162	23.444	3.5	1.0	115.8	173.3	27.3	0.44	1.4	1.41
395A/394A	66.675	110.000	22.000	21.996	18.824	0.8	1.3	88.5	119.3	21.1	0.40	1.5	0.79
395CS/394CS	66.675	113.487	23.448	23.444	18.824	3.5	1.3	88.5	119.3	21.1	0.40	1.5	0.92
395S/394A	66.675	110.000	22.000	21.996	18.824	3.5	1.3	88.5	119.3	21.1	0.40	1.5	0.79
395S/394AS	66.675	110.000	22.000	21.996	18.824	3.5	3.3	88.5	119.3	21.1	0.40	1.5	0.79
3984/3920	66.675	112.712	30.162	30.048	23.812	3.5	3.3	109.9	163.4	25.8	0.40	1.5	1.16
3994/3920	66.675	112.712	30.162	30.048	23.812	5.5	3.3	109.9	163.4	25.8	0.40	1.5	1.15
HM212049/HM212011	66.675	122.238	38.100	38.354	29.718	3.5	3.3	193.0	253.8	26.9	0.34	1.8	1.81
399AS/394A	68.262	110.000	22.000	21.996	18.824	5.0	1.3	88.5	119.3	21.1	0.40	1.5	0.76
9278/9220	68.262	161.925	49.212	46.038	31.750	3.5	3.3	265.2	317.2	50.1	0.71	0.8	4.62
33275/33462	69.850	117.475	30.162	30.162	23.812	3.5	3.3	115.8	173.3	27.7	0.44	1.4	1.25
33275/33472	69.850	120.000	29.794	30.162	23.444	3.5	1.0	115.8	173.3	27.3	0.44	1.4	1.32

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
47487/47420A	69.850	120.000	32.545	32.545	26.195	3.5	0.7	142.0	233.0	26.4	0.36	1.7	1.49
482/472X	69.850	123.825	30.162	29.007	24.605	3.6	3.2	118.0	161.0	26.0	1.56	1.6	1.27
566/563	69.850	127.000	36.512	36.170	28.575	3.6	3.2	156.0	226.0	28.6	0.36	1.7	1.89
655/653	69.850	146.050	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	3.24
H913849/H913810	69.850	146.050	41.275	39.688	25.400	3.5	3.3	205.3	242.4	45.1	0.78	0.8	2.87
34274/34478	69.952	121.442	24.608	23.012	17.462	2.0	2.0	90.0	127.0	26.8	0.45	1.3	1.08
H916642/H916610	70.000	176.212	54.770	53.183	36.512	3.3	3.3	315.7	398.3	52.6	0.70	0.9	6.40
JLM813049/JLM813010	70.000	110.000	26.000	25.000	20.500	1.0	2.5	103.0	158.0	26.2	0.49	1.2	0.88
JM612949/JM612910	70.000	115.000	29.000	29.000	23.000	3.0	2.5	128.9	180.0	26.2	0.43	1.4	1.11
JW7049/JW7010	70.000	140.000	39.000	35.500	27.000	3.0	3.0	181.9	248.2	48.3	0.87	0.7	2.60
33281/33462	71.438	117.475	30.162	30.162	23.812	3.5	3.3	115.8	173.3	27.7	0.44	1.4	1.21
33281/33472	71.438	120.000	29.794	30.162	23.444	3.5	1.0	115.8	173.3	27.3	0.44	1.4	1.28
567A/563	71.438	127.000	36.512	36.170	28.575	3.6	3.2	156.0	226.0	28.6	0.36	1.7	1.84
H414249/H414210	71.438	136.525	41.275	41.275	31.750	3.6	3.2	241.0	308.0	30.2	0.36	1.7	2.64
H715345/H715311	71.438	136.525	46.038	46.038	36.512	3.6	3.2	231.0	369.0	37.0	0.47	1.3	3.27
HM813849/HM813811	71.438	127.000	36.512	36.512	26.988	3.6	1.6	166.0	235.0	32.9	0.50	1.2	2.28
29685/29620	73.025	112.712	25.400	25.400	19.050	3.5	3.3	95.5	150.4	26.2	0.49	1.2	0.88
33287/33462	73.025	117.475	30.162	30.162	23.812	3.5	3.3	115.8	173.3	27.7	0.44	1.4	1.17
567/563	73.025	127.000	36.512	36.170	28.575	3.6	3.2	156.0	226.0	28.6	0.36	1.7	1.79
6460/6420	73.025	149.225	53.975	54.229	44.450	3.6	3.2	285.0	404.0	39.3	0.35	1.7	4.39
657/653	73.025	146.050	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	3.12
762/752	73.025	161.925	47.625	48.260	38.100	3.6	3.2	273.0	391.0	35.5	0.34	1.8	4.79
29688/26920	73.817	112.712	25.400	25.400	19.050	1.6	3.2	97.0	155.0	26.2	0.49	1.2	0.86
568/563	73.817	127.000	36.512	36.170	28.575	0.8	3.2	156.0	226.0	28.6	0.36	1.7	1.78
JH745647/JH415610	75.000	145.000	51.000	51.000	42.000	3.0	2.5	290.0	412.0	36.5	0.36	1.7	3.79
JLM714149/JLM714110	75.000	115.000	25.000	25.000	19.000	3.0	2.5	102.9	153.2	25.4	0.46	1.3	0.85
JM714249/JM714210	75.000	120.000	31.000	29.500	25.000	3.0	2.5	135.3	205.8	28.8	0.44	1.4	1.28
27684/27620	76.200	125.412	25.400	25.400	19.845	3.5	1.5	103.9	166.2	25.8	0.42	1.4	1.23

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
34301/34478	76.200	121.442	24.608	23.012	17.462	3.6	2.0	90.0	127.0	26.8	0.45	1.3	0.94
42687/42620	76.200	127.000	30.162	31.000	22.225	3.5	3.3	131.0	210.0	27.1	0.42	1.4	1.46
42688/42620	76.200	127.000	30.162	31.000	22.225	6.4	3.3	131.0	210.0	27.1	0.42	1.4	1.44
47678/47620	76.200	133.350	33.338	33.338	26.195	6.4	3.3	143.6	244.9	29.3	0.40	1.5	1.89
495A/493	76.200	136.525	30.162	29.769	22.225	3.5	3.3	135.7	201.9	28.8	0.44	1.4	1.82
5760/5735	76.200	135.733	44.450	46.101	34.925	3.6	3.2	213.0	337.0	32.9	0.41	1.5	2.70
6461/6420	76.200	149.225	53.975	54.229	44.450	3.6	3.2	285.0	404.0	39.3	0.36	1.7	4.23
659/652	76.200	152.400	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	3.01
HH221430/HH221410	76.200	190.500	57.150	57.531	46.038	3.6	3.2	440.0	602.0	42.4	0.33	1.8	8.86
42690/42620	77.455	127.000	30.162	31.000	22.225	3.6	3.2	143.0	225.0	27.0	0.42	1.4	1.37
34306/34478	77.788	121.442	24.608	23.012	17.462	3.6	2.0	90.0	127.0	26.8	0.45	1.3	0.91
34307/34478	77.788	121.442	24.608	23.012	17.462	6.4	2.0	90.0	127.0	26.8	0.45	1.3	0.88
LM814849/LM814810	77.788	117.475	25.400	25.400	19.050	3.6	3.2	101.0	166.0	27.5	0.51	1.2	0.89
661/653	79.375	146.050	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	2.88
756A/752	79.375	161.925	47.625	48.260	38.100	7.9	3.2	273.0	391.0	35.5	0.34	1.8	4.48
HH221431/HH221410	79.375	190.500	57.150	57.531	46.038	3.6	3.2	440.0	602.0	42.4	0.33	1.8	8.69
98316/98788	80.000	200.000	52.761	49.212	34.925	3.6	3.2	347.0	471.0	54.6	0.63	1.0	8.01
JM515649/JM515610	80.000	130.000	35.000	34.000	28.500	3.2	2.5	168.0	256.0	29.6	0.39	1.5	1.70
JW8049/JW8010	80.000	160.000	45.000	41.000	31.000	3.0	3.0	232.0	320.5	54.7	0.87	0.7	3.93
496/492A	80.962	133.350	30.162	29.769	22.225	3.6	3.2	133.0	198.0	29.8	0.44	1.4	1.64
27687/27620	82.550	125.412	25.400	25.400	19.845	3.5	1.5	103.9	166.2	25.8	0.42	1.4	1.07
47686/47620	82.550	133.350	33.338	33.338	26.195	-	-	143.6	244.9	29.3	0.40	1.5	1.70
47686/47620A	82.550	133.350	33.338	33.338	26.195	3.5	0.8	143.6	244.9	29.3	0.40	1.5	1.72
47687/47620	82.550	133.350	33.338	33.338	26.195	6.8	3.3	143.6	244.9	29.3	0.40	1.5	1.68
495/492A	82.550	133.350	30.162	29.769	22.225	3.6	3.2	133.0	198.0	29.8	0.44	1.4	1.59
580/572	82.550	139.992	36.512	36.098	28.575	3.5	3.3	177.6	265.2	31.0	0.40	1.5	2.22
580/572X	82.550	139.700	36.512	36.098	28.575	3.5	3.3	177.6	265.2	31.0	0.40	1.5	2.21
663/653	82.550	146.050	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	2.75

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
757/752	82.550	161.925	47.625	48.260	38.100	3.6	3.2	273.0	391.0	35.5	0.34	1.8	4.38
HM516448/HM516410	82.550	133.350	39.688	39.688	32.545	6.7	3.2	177.0	306.0	32.2	0.40	1.5	2.08
27689/27620	83.345	125.412	25.400	25.400	19.845	0.8	1.6	101.0	162.0	24.7	0.42	1.4	1.03
27690/27620	83.345	125.412	25.400	25.400	19.845	3.6	1.6	101.0	162.0	24.7	0.42	1.4	1.02
27691/27620	83.345	125.412	25.400	25.400	19.845	6.4	1.6	101.0	162.0	24.7	0.42	1.4	0.99
498/492A	84.138	133.350	30.162	29.769	22.225	3.6	3.2	133.0	198.0	29.8	0.44	1.4	1.54
27695/27620	85.000	125.412	25.400	25.400	19.845	5.0	1.5	103.9	166.2	25.8	0.42	1.4	1.00
98335/98788	85.000	200.000	52.761	49.212	34.925	3.6	3.2	347.0	471.0	54.5	0.63	1.0	7.76
JH217249/JH217210	85.000	150.000	46.000	46.000	38.000	3.0	2.5	274.0	390.0	33.6	0.33	1.8	3.33
JHM516849/JHM516810	85.000	140.000	39.000	38.000	31.500	3.0	2.5	203.0	308.0	32.8	0.41	1.5	2.26
JM716649/JM716610	85.000	130.000	30.000	29.000	24.000	3.0	2.5	142.5	228.0	29.5	0.44	1.4	1.38
497/492A	85.725	133.350	30.162	29.769	22.225	3.6	3.2	133.0	198.0	29.8	0.44	1.4	1.39
497A/493	85.725	136.525	30.162	29.769	22.225	6.4	3.2	133.0	198.0	29.8	0.44	1.4	1.50
596/592A	85.725	152.400	39.688	36.322	30.162	3.5	3.3	184.3	288.9	37.4	0.44	1.4	2.89
665/653	85.725	146.050	41.275	41.275	31.750	3.6	3.2	208.0	301.0	33.6	0.41	1.5	2.61
677/672	85.725	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.6	0.47	1.3	4.12
758/752	85.725	161.925	47.625	48.260	38.100	3.6	3.2	273.0	391.0	35.5	0.34	1.8	4.22
HM617049/HM617010	85.725	142.138	42.862	42.862	34.133	4.8	3.2	219.0	351.0	35.2	0.43	1.4	2.71
42350/42584	88.900	148.430	28.575	28.971	21.433	3.0	3.0	143.5	225.5	31.8	0.49	1.2	1.94
593/592A	88.900	152.400	39.688	36.322	30.162	3.5	3.3	184.3	288.9	37.4	0.44	1.4	2.77
593A/592A	88.900	152.400	39.688	36.322	30.162	6.4	3.3	184.3	288.9	37.4	0.44	1.4	2.75
6580/6535	88.900	161.925	53.975	55.100	42.862	3.5	3.3	311.7	470.1	40.9	0.40	1.5	4.69
679/672	88.900	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.6	0.47	1.3	4.01
759/752	88.900	161.925	47.625	48.260	38.100	3.6	3.2	273.0	391.0	35.5	0.34	1.8	4.06
98350/98788	88.900	200.000	52.761	49.212	34.925	3.6	3.2	347.0	471.0	54.6	0.63	1.0	7.55
HH221434/HH221410	88.900	190.500	57.150	57.531	46.038	7.9	3.2	440.0	602.0	42.4	0.33	1.8	8.06
HM518445/HM518410	88.900	152.400	39.688	39.688	30.163	6.4	3.3	234.0	373.0	33.4	0.40	1.5	2.84
L217849/L217810	88.900	123.825	20.638	20.638	16.670	1.6	1.6	81.8	145.0	20.7	0.33	1.8	0.47

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
HM218248/HM218210	89.974	146.975	40.000	40.000	32.500	7.1	3.6	206.0	310.0	30.8	0.33	1.8	2.36
HM218248/HM218210(T)	90.000	147.000	40.000	40.000	32.500	7.0	3.5	233.2	351.1	31.3	0.33	1.8	0.48
J90354/J90748	90.000	190.000	50.800	46.038	31.750	3.5	3.3	278.1	359.3	64.5	0.87	0.7	5.98
JHM318448/JHM318410	90.000	155.000	44.000	44.000	35.500	3.0	2.5	290.0	407.0	33.6	0.34	1.8	3.30
JM718149/JM718110	90.000	145.000	35.000	34.000	27.000	3.0	2.5	194.0	291.0	32.7	0.44	1.4	2.12
760/752	90.488	161.925	47.625	48.260	38.100	3.6	3.2	273.0	391.0	35.5	0.34	1.8	3.97
598/592A	92.075	152.400	39.688	36.322	30.162	3.5	3.3	184.3	288.9	37.4	0.44	1.4	2.64
598A/592A	92.075	152.400	39.688	36.322	30.162	6.4	3.3	184.3	288.9	37.4	0.44	1.4	2.62
598A/593X	92.075	150.000	35.992	36.322	27.000	6.4	3.0	184.3	288.9	33.7	0.44	1.4	2.33
681/672	92.075	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.6	0.47	1.3	3.83
778/772	92.075	180.975	47.625	48.006	38.100	3.6	3.2	288.0	438.0	39.4	0.39	1.6	5.57
JL819349/JL819310	95.000	135.000	20.000	20.000	14.000	5.0	2.5	83.0	168.9	31.0	0.58	1.0	0.84
JM719149/JM719113	95.000	150.000	35.000	34.000	27.000	3.0	2.5	187.0	294.0	33.5	0.44	1.4	2.17
52375/52618	95.250	157.162	36.512	36.116	26.195	3.6	3.2	180.0	288.0	36.0	0.47	1.3	2.66
594/593X	95.250	150.000	35.992	36.322	27.000	3.5	3.0	184.3	288.9	33.7	0.44	1.4	2.22
594A/592A	95.250	152.400	39.688	36.322	30.162	5.0	3.3	184.3	288.9	37.4	0.44	1.4	2.51
683/672	95.250	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.6	0.47	1.3	3.68
864/854	95.250	190.500	57.150	57.531	44.450	8.0	3.3	396.9	584.5	41.4	0.33	1.8	7.27
HH221440/HH221410	95.250	190.500	57.150	57.531	46.038	7.9	3.2	440.0	602.0	42.5	0.33	1.8	7.64
L319249/L319210	95.250	130.175	20.638	21.432	16.670	1.6	1.6	97.0	167.0	22.2	0.35	1.7	0.79
LL319349/LL319310	95.250	128.588	15.875	15.083	11.908	1.6	1.6	58.0	93.0	20.3	0.35	1.7	0.53
685/672	98.425	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.7	0.47	1.3	3.52
HH221442/HH221410	98.425	190.500	57.150	57.531	46.038	3.6	3.2	440.0	602.0	42.4	0.33	1.8	7.49
HH224334/HH224310	99.975	212.725	66.675	66.675	53.975	3.6	3.2	513.0	699.0	46.7	0.33	1.8	11.7
HH221447/HH221410	99.982	190.500	57.150	57.531	46.038	6.4	3.2	440.0	602.0	42.5	0.33	1.8	7.34
HM220149/HM220110	100.000	157.000	42.000	42.000	34.000	8.0	3.5	257.4	419.6	32.4	0.33	1.8	2.90
JHM720249/JHM720210	100.000	160.000	41.000	40.000	32.000	3.0	2.5	257.1	417.9	38.7	0.47	1.3	3.06
JP10049/JP10010	100.000	145.000	24.000	22.500	17.500	3.0	3.0	113.6	165.4	30.3	0.47	1.3	1.16

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
52393/52618	100.012	157.162	36.512	36.116	26.195	3.6	3.2	180.0	288.0	36.0	0.47	1.3	2.46
52400/52618	101.600	157.162	36.512	36.116	26.195	3.6	3.2	180.0	288.0	36.0	0.47	1.3	2.39
687/672	101.600	168.275	41.275	41.275	30.162	3.6	3.2	224.0	349.0	38.6	0.47	1.3	3.36
780/772	101.600	180.975	47.625	48.006	38.100	3.6	3.2	288.0	438.0	39.4	0.39	1.6	5.02
98400/98788	101.600	200.000	52.761	49.212	34.925	3.6	3.2	347.0	471.0	54.6	0.63	1.0	6.82
HH221449/HH221410	101.600	190.500	57.150	57.531	46.038	7.9	3.2	440.0	602.0	42.4	0.33	1.8	7.20
HH224335/HH224310	101.600	212.725	66.675	66.675	53.975	7.1	3.2	513.0	699.0	46.7	0.33	1.8	11.5
HH923649/HH923610	101.600	250.825	76.200	73.025	50.800	6.4	6.4	548.0	691.0	73.8	0.71	0.9	17.40
71412/71750	104.775	190.500	47.625	49.212	34.925	3.6	3.2	303.0	483.0	40.9	0.42	1.4	5.77
782/772	104.775	181.000	47.625	48.006	38.100	3.5	3.3	283.0	430.0	40.5	0.39	1.6	4.85
37425/37625	107.950	158.750	23.020	21.438	15.875	3.5	3.3	104.7	171.5	36.4	0.61	1.0	1.36
48190/48120	107.950	161.925	34.925	34.925	26.988	3.6	3.2	173.0	293.0	38.4	0.51	1.2	2.34
71425/71750	107.950	190.500	47.625	49.212	34.925	3.6	3.2	303.0	483.0	40.9	0.42	1.4	5.56
936/932	107.950	212.725	66.675	66.675	53.975	7.9	3.2	450.0	674.0	47.5	0.33	1.8	10.4
HH224340/HH224310	107.950	212.725	66.675	66.675	53.975	7.9	3.2	513.0	699.0	46.7	0.33	1.8	11.0
37431A/37625	109.538	158.750	23.020	21.438	15.875	5.0	3.3	104.7	171.5	36.4	0.61	1.0	1.31
LM522548/LM522510	109.987	159.987	34.925	34.925	26.988	7.9	3.2	184.0	319.0	32.9	0.40	1.5	2.20
LM522549/LM522510	109.987	159.987	34.925	34.925	26.988	3.6	3.2	184.0	319.0	32.9	0.40	1.5	2.27
JHM522649/JHM522610	110.000	180.000	47.000	46.000	38.000	3.0	2.5	306.0	487.0	40.5	0.41	1.5	4.51
JM822049/JM822010	110.000	165.000	35.000	35.000	26.500	3.0	2.5	198.9	332.6	38.0	0.50	1.2	2.58
68450/68712	114.300	180.975	34.925	31.750	25.400	3.6	3.2	171.0	247.0	40.7	0.50	1.2	2.88
71450/71750	114.300	190.500	47.625	49.212	34.925	3.6	3.2	33.0	483.0	40.9	0.42	1.4	5.14
938/932	114.300	212.725	66.675	66.675	53.975	7.1	3.2	450.0	674.0	47.5	0.33	1.8	9.84
HH224346/HH224310	114.300	212.725	66.675	66.675	53.975	7.1	3.2	513.0	699.0	46.7	0.33	1.8	10.4
HH926744/HH926710	114.300	273.050	82.550	82.550	53.975	6.4	6.4	707.0	898.0	76.0	0.63	1.0	22.7
HM926740/HM926710	114.300	228.600	53.975	49.428	38.100	3.6	3.2	430.0	651.0	58.0	0.74	0.8	9.67
HH224349/HH224310	114.976	212.725	66.675	66.675	53.975	7.1	3.2	513.0	699.0	46.7	0.33	1.8	10.3
71455/71750	115.087	190.500	47.625	49.212	34.925	8.0	3.3	307.4	487.3	40.8	0.42	1.4	4.99

轴承型号	外形尺寸(mm)							额定载荷(kN)		装配高(mm)	常数	轴向载荷系数	参考重量(kg)
	d	D	T	B	C	R	r	Cr	Cor	a	e	Y1	
68462/68712	117.475	180.975	34.925	31.750	25.400	3.6	3.2	171.0	247.0	40.7	0.50	1.2	2.74
68463/68712	117.475	180.975	34.925	31.750	25.400	7.9	3.2	171.0	247.0	40.6	0.50	1.2	2.66
HH228340/HH228310	120.650	254.000	77.788	82.550	61.912	9.5	6.4	717.0	1050.0	54.0	0.32	1.9	19.4
HM624749/HM624710	120.650	190.500	46.038	46.038	34.925	3.6	1.6	313.0	512.0	41.6	0.43	1.4	4.66
HH228349/HH228310	127.000	254.000	77.788	82.550	61.912	9.5	6.4	717.0	1050.0	54.0	0.32	1.9	18.6
LL225749/LL225710	127.000	165.895	18.258	17.462	13.495	1.5	1.5	82.7	149.4	24.3	0.33	1.8	0.91
48684/48620	142.875	200.025	41.275	39.688	34.130	7.9	3.2	246.0	491.0	38.6	0.34	1.8	3.74
48685/48620	142.875	200.025	41.275	39.688	34.130	3.6	3.2	246.0	491.0	38.6	0.34	1.8	3.83
46790/46720	165.000	225.425	41.275	39.688	33.338	3.5	3.3	262.8	577.0	44.0	0.38	1.6	4.64