

| 轴承型号 | 外型尺寸 (mm) |     |    |     |     | 额定基本径向负荷 (KN) |      | 重量 (kg) |
|------|-----------|-----|----|-----|-----|---------------|------|---------|
|      | d         | D   | B  | R   | r   | Cr            | Cor  |         |
| 6002 | 15        | 32  | 9  | 0.3 | 0.3 | 5.59          | 2.86 | 0.031   |
| 6003 | 17        | 35  | 10 | 0.3 | 0.3 | 6             | 3.27 | 0.040   |
| 6004 | 20        | 42  | 12 | 0.6 | 0.6 | 9.4           | 5.05 | 0.068   |
| 6005 | 25        | 47  | 12 | 0.6 | 0.6 | 10.1          | 5.85 | 0.078   |
| 6006 | 30        | 55  | 13 | 1.0 | 1.0 | 13.2          | 8.3  | 0.110   |
| 6007 | 35        | 62  | 14 | 1.0 | 1.0 | 16            | 10.3 | 0.148   |
| 6008 | 40        | 68  | 15 | 1.0 | 1.0 | 16.8          | 11.5 | 0.185   |
| 6009 | 45        | 75  | 16 | 1.0 | 1.0 | 21            | 15.1 | 0.230   |
| 6010 | 50        | 80  | 16 | 1.0 | 1.0 | 21.8          | 16.6 | 0.258   |
| 6011 | 55        | 90  | 18 | 1.1 | 1.1 | 28.3          | 21.2 | 0.362   |
| 6012 | 60        | 95  | 18 | 1.1 | 1.1 | 29.5          | 23.2 | 0.385   |
| 6013 | 65        | 100 | 18 | 1.1 | 1.1 | 30.5          | 25.2 | 0.410   |
| 6202 | 15        | 35  | 11 | 0.6 | 0.6 | 7.64          | 3.72 | 0.045   |
| 6203 | 17        | 40  | 12 | 0.6 | 0.6 | 9.6           | 4.6  | 0.064   |
| 6204 | 20        | 47  | 14 | 1.0 | 1.0 | 12.8          | 6.65 | 0.103   |
| 6205 | 25        | 52  | 15 | 1.0 | 1.0 | 14            | 7.85 | 0.127   |
| 6206 | 30        | 62  | 16 | 1.0 | 1.0 | 19.5          | 11.3 | 0.200   |
| 6207 | 35        | 72  | 17 | 1.1 | 1.1 | 25.7          | 15.3 | 0.288   |

|      |    |     |    |     |     |       |      |       |
|------|----|-----|----|-----|-----|-------|------|-------|
| 6208 | 40 | 80  | 18 | 1.1 | 1.1 | 29.1  | 17.8 | 0.368 |
| 6209 | 45 | 85  | 19 | 1.1 | 1.1 | 32.5  | 20.4 | 0.416 |
| 6210 | 50 | 90  | 20 | 1.1 | 1.1 | 35    | 23.2 | 0.463 |
| 6211 | 55 | 100 | 21 | 1.5 | 1.5 | 43.5  | 29.2 | 0.603 |
| 6302 | 15 | 42  | 13 | 1.0 | 1.0 | 11.5  | 5.42 | 0.080 |
| 6303 | 17 | 47  | 14 | 1.0 | 1.0 | 13.5  | 6.55 | 0.109 |
| 6304 | 20 | 52  | 15 | 1.1 | 1.1 | 15.9  | 7.9  | 0.142 |
| 6305 | 25 | 62  | 17 | 1.1 | 1.1 | 21.2  | 10.9 | 0.219 |
| 6306 | 30 | 72  | 19 | 1.1 | 1.1 | 26.7  | 15   | 0.349 |
| 6307 | 35 | 80  | 21 | 1.5 | 1.5 | 33.5  | 19.1 | 0.455 |
| 6308 | 40 | 90  | 23 | 1.5 | 1.5 | 40.75 | 24   | 0.639 |
| 6309 | 45 | 100 | 25 | 1.5 | 1.5 | 52.86 | 32   | 0.837 |